

TRIAC air filter regulator FR-10 is a quality unit essential to protect positioners, solenoid valves, and actuators from dirt, foreign particles, and moisture and to provide constant and reliable control under variable flow rates and supply pressures

FEATURES

- > Stable setting pressure for constant output pressure
- ➤ Corrosion-resistant construction
- ➤ High capacity 5 micron filter
- ➤ Self-relief function for balance of output and setting pressures
- High flow capacity

SPECIFICATIONS

Port size	1/4" NPT
Fluid	Air
Output range	08bar (120psi)
Max. Supply pressure	15bar (225psi)
Ambient and fluid temperature	Max. 70°C (no freezing)
Gauge port size	1/8" NPT
Filtration	5 Micron
Pressure gauge material	Stainless steel
Body material	Aluminum diecast
Weight (kg)	0.4 (with pressure gauge)

FR-10

HOW TO ORDER

FR-10

Pressure Gauge Mounting Bracket

Description	Code
- Port Size	1/4" NPT
- Pressure Gauge	None G: 10bar (150psi)
- Color	Black
- Mounting Bracket	None B: L-type



11363 Deerfield Road Cincinnati, Ohio 45242 Phone: 513.247.5465 Fax: 513.247.5462

INTERNAL VIEW AND DIMENSIONS

