



MODEL NO.

**21-11516-A2**

PRODUCT LINE

**GO Switch Leverless Limit Switches**

SPECIFICATIONS

- Model** GO Switch Model 21- 1-1/2" square x 3-13/16" overall
- Contact Form** SPDT (Form C) contacts;  
10A/120VAC,3A/24VDC
- Sensing Range** Standard sensing - approx. 10mm (3/8") side sensing
- Outlet Position** 1/2" NPT conduit outlet on bottom of enclosure
- Enclosure Material** Brass - coated with flat black lacquer
- Approvals** CSA / FM explosion proof - CI I, Div 2; Grps A-D; CI II, Div 2, Grps E-G; CI III (Lead seal req'd within 18")
- Wiring Options** PVC Lead Wires - 18 gauge - 914mm (36")
- Temperature Rating** -40 °C - 105 °C

**4 Wire PVC & HiTemp Leads**

N/C	Red
N/O	Blue
COM	Black
GND	Green



**Terminations A & F**

S-K025 Rev. 4, 0406-5M

Current as of Mar 24, 2011 - subject to change without notice.

**TOPWORX**

TopWorx, Inc. (502) 969-8000 ph.  
3300 Fern Valley Rd. (502) 969-5911 fax  
Louisville, KY 40213 www.topworx.com