



3A@24VDC

MODEL NO.

**81-20524-A2**

PRODUCT LINE

**GO Switch Leverless Limit Switches**

SPECIFICATIONS

**Model** GO Switch Model 81- 1-1/2" square x 4 7/8".  
 Subtract 1/2" from length for side conduit

**Contact Form** DPDT (Form CC) 10A@120VAC /

**Sensing Range** Approx. 6mm (1/4") end sensing

**Outlet Position** Bottom of enclosure - 1/2" NPT

**Enclosure Material** Stainless steel

**Approvals** CSA/FM Explosion Proof CI I, Div 1; Grps A-D; CI II, Div 1, Grps E-G; CI III (lead seal req'd within 18")

**Wiring Options** PVC Lead Wires - 18 gauge - 914mm (36")

**Temperature Rating** -40 °C - 105 °C

PVC & Teflon Leads	
N/C1 - Red	N/C2 - Red/White Stripe
N/O1 - Blue	N/O2 - Blue/White Stripe
COM1 - Black	COM2 - Black/White Stripe
(CSA approvals only) GND - Green	

Termination A & F



S-K025 Rev. 4, 0406-5M  
L-L098

Current as of Mar 24, 2011 - subject to change without notice.

**TOPWORX**

TopWorx, Inc. (502) 969-8000 ph.  
 3300 Fern Valley Rd. (502) 969-5911 fax  
 Louisville, KY 40213 www.topworx.com